

# Compression Connector DIN 46267-2, Al 240 mm<sup>2</sup> RM/SM + 300 mm<sup>2</sup> SE

for non-tension connections.

For DIN 48201 compliant circular stranded aluminium conductors and circular stranded/sector-shaped stranded, circular solid and sector-shaped solid aluminium conductors in compliance with DIN VDE 0295.

Circular solid and sector-shaped solid aluminium conductors are to be compressed with mechanical crimping pliers only.

Sector-shaped conductors must be rounded with round-forming dies.  
Al compression connectors are supplied prefilled with compression compound and packed in heat-sealed plastic bags.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>300 977 977</b>
<b>Type</b>	<b>non-tension Al</b>
<b>Conductor cross section Al stranded circular</b>	(mm <sup>2</sup> ) 240
<b>Conductor cross section Al solid sector-shaped</b>	(mm <sup>2</sup> ) 300
<b>Conductor cross section Al stranded sector-shaped</b>	(mm <sup>2</sup> ) 240
<b>Diameter of conductor</b>	Ø (mm) 17,8 - 20,6
<b>Material</b>	Al
<b>Surface</b>	uncoated
<b>Code number</b>	32
<b>Number of compressions, mech. / hydr.</b>	8-8/3-3
<b>Blind hole</b>	no

## Dimensions

<b>Dimension D</b>	<b>d (mm)</b>	<b>21,5</b>
<b>Dimension L</b>	<b>(mm)</b>	<b>145</b>