

ISICOMPACT S FS

The ISICOMPACT product family is the answer from PFISTERER, the inventor of multi-core cable junction technology, to modern labour standards and is perfect for live-line working.

The patented design offers the following advantages compared to conventional clamping rings:

- Single-screw solution with built-in torque wrench
- IP2X contact protection against electrical hazards during all assembly steps
- Stripping of tap conductors no longer necessary
- Tap conductors are inserted, laborious threading from the front no longer required
- Flexible pressure plates ensure a continuous contact force
- Reduced variant diversity due to broad application areas
- Compact designs
- Suitable for all cable conductor types (EN 60228 - N(A)YY, N(A)2XY, N(A)KBA, N(A)Y2Y, N(A)2X2Y)

The ISICOMPACT S FS has a special fixing wedge and thus is suitable for cables with up to 4 control conductors.



Picture may vary.

Technical Data

Article no.		331 896 015
Number of wires		4
Conductor cross section Al solid circular	(mm ²)	35 - 95
Conductor cross section Cu solid circular	(mm ²)	35 - 95
Conductor cross section Al solid sector-shaped	(mm ²)	35 - 95
Conductor cross section Al stranded circular	(mm ²)	25 - 95
Conductor cross section Cu stranded circular	(mm ²)	25 - 95
Conductor cross section Al stranded sector-shaped	(mm ²)	35 - 95
Conductor cross section Cu stranded sector-shaped	(mm ²)	35 - 95
Cross section of tap conductor	(mm ²)	6 - 50 + 70 SE
Width across flats	(SW)	13
Circumscribed circle diameter	(mm)	85 - 100
Screw length	(mm)	130
Matching joint set		AM 130/300, AM 140/420N, AM 140/420K