

## LV Piercing Connector Type 4 / L

Insulated screw connectors for low voltage cables with insulation-piercing contact geometry and shear bolts. The patented screw design ensures that the conductor is not damaged during installation. The connector has been designed so that contact protection as per IP2X is provided during the entire assembly sequence and there is also no danger of a short circuit.

### Advantages:

- Piercing connector – no stripping of the individual wires with PVC, XLPE and PILC insulation
- Electrically and mechanically tested in accordance with IEC 61238-1 class A for conductors of class 1 and 2
- IP2X contact protection according to DIN EN 60529 during all assembly steps
- Creepage distance according to DIN EN 60664 - degree of pollution 1
- Easy, safe installation – ideal for live-line working
- Assembly with standard tools
- Designed for resin based and heat shrink joints
- Shear bolts prevent assembly errors
- Compact design

### Material:

- Body: Aluminium, tinned
- Bolt: Aluminium, uncoated



Picture may vary.

## Technical Data

Article no.	332 710 040	
Conductor cross section Al RE	(mm <sup>2</sup> )	50 - 120
Conductor cross section Al RM	(mm <sup>2</sup> )	50 - 120
Conductor cross section Al SE	(mm <sup>2</sup> )	50 - 150
Conductor cross section Al SM	(mm <sup>2</sup> )	50 - 120
Conductor cross section Cu RE	(mm <sup>2</sup> )	35 - 120
Conductor cross section Cu RM	(mm <sup>2</sup> )	35 - 120
Conductor cross section Cu SM	(mm <sup>2</sup> )	35 - 120
Number of screws		2
Shear-off torque	(Nm)	24 - 30
Surface		tin-plated
Width across flats		SW 16
Screw Type		shear bolt
Inspection hole		yes

<b>Article no.</b>	<b>332 710 040</b>
<b>Blind hole</b>	<b>no</b>

## Dimensions

<b>Length</b>	<b>(mm)</b>	<b>114</b>
<b>Width</b>	<b>(mm)</b>	<b>40</b>
<b>Height</b>	<b>(mm)</b>	<b>44 (88 unmounted)</b>
<b>Core diameter</b>	<b>Ø (mm)</b>	<b>24 / 18 (sector-shaped conductor hole)</b>