

# Single-Pole Earthing and Short-Circuiting Device



Picture may vary.

## Technical Data

|                                      |                          |             |
|--------------------------------------|--------------------------|-------------|
| <b>Article no.</b>                   | <b>369 201 001 04170</b> |             |
| <b>Earthing Clamp</b>                | <b>U3</b>                |             |
| <b>Clamping range earthing clamp</b> | <b>2 - 20</b>            |             |
| <b>for ball pin diameter</b>         | <b>Ø (mm)</b>            | <b>20</b>   |
| <b>for T-bolt diameter</b>           | <b>Ø (mm)</b>            | <b>15</b>   |
| <b>Line clamp</b>                    | <b>P3D</b>               |             |
| <b>Clamping range line clamp</b>     | <b>2 - 20</b>            |             |
| <b>for ball pin diameter</b>         | <b>Ø (mm)</b>            | <b>20</b>   |
| <b>for T-bolt diameter</b>           | <b>Ø (mm)</b>            | <b>15</b>   |
| <b>Earthing cable cross section</b>  | <b>(mm<sup>2</sup>)</b>  | <b>95</b>   |
| <b>Cable length</b>                  | <b>(m)</b>               | <b>1,5</b>  |
| <b>Max. short-circuit current</b>    | <b>(kA)</b>              | <b>18,7</b> |
| <b>Insulating material</b>           | <b>PVC transparent</b>   |             |
| <b>Language</b>                      | <b>German, English</b>   |             |