Voltage detector KP-Test 5R+ 15 kV for Catenaries, Two-Parts

The **KP-Test 5R+ 15 kV 16,7 Hz** capacitive voltage detector is designed for use on railway catenaries. It indicates the presence of operating voltage when brought into contact with the conductor.

Technical Description:

- Bright LEDs for clear recognition
- Particularly loud, integrated audible signal
- Extensive self-test functions at switch-on
- Contact electrode in hook form with contact pin for optimum contact with the catenary
- For single-phase networks
- New, simple and intuitive to use plug-in system with a large, blue, easy-to-use push button
- Consistent colouring of fibre glass tube in yellow

The **KP-Test 5R+ 15 kV 16,7 Hz** is built in accordance to DIN VDE 0681, Part 6.

Versions in other languages or with other signal mode are available on request.

Picture may vary.



Technical Data

Article no.		930 310 002 00002
Nominal voltage	U _n (kV)	15
Nominal frequency	f _N (Hz)	16.7
Suitable bag		B3
Carrying bag included		yes
Voltage type		AC
Area of application		Catenary Wires
Language on labels		de
Туре		KP-Test 5R+

Dimensions

Total length	L _G (mm)	4795
Transporting length	L _T (mm)	2440
Diameter of insulating element	d (mm)	33