

# Warning Sphere

## PA6, glass fiber reinforced, white

### Features:

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.



Picture may vary.

### Material:

- **Clamps:**  
Aluminium alloy with grooved channel
- **Hemisphere:**  
Coloured Polyamide 6 (PA6), glass fiber reinforced
- **Plates:**  
Stainless steel
- **Bolts:**  
Stainless steel
- **Safety plate:**  
Stainless steel

## Technical Data

<b>Article no.</b>		<b>180 542 350</b>
<b>Conductor diameter range</b>	(mm)	6.6 - 8.0
<b>Conductor diameter range</b>	(inch)	0.26 - 0.31
<b>Colour</b>		white
<b>Warning sphere material</b>		Polyamide 6 (PA6), glass fiber reinforced
<b>Clamp material</b>		Aluminium

## Dimensions

<b>Warning sphere diameter</b>	(mm)	600
<b>Warning sphere diameter</b>	(inch)	23.6