PFISTERER

# Warning Sphere
# PA6, glass fiber reinforced, red / white

**Features:**

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.

*Picture may vary.*

**Material:**

- **Clamps:**
  Aluminium alloy with grooved channel
- **Hemisphere:**
  Coloured Polyamide 6 (PA6), glass fiber reinforced
- **Plates:**
  Stainless steel
- **Bolts:**
  Stainless steel
- **Safety plate:**
  Stainless steel

## Technical Data

| Article no. | | 180 542 477 |
|---|---|---|
| Conductor diameter range | (mm) | 41.8 - 43.1 |
| Conductor diameter range | (inch) | 1.65 - 1.70 |
| Colour | | red / white |
| Warning sphere material | | Polyamide 6 (PA6), glass fiber reinforced |
| Clamp material | | Aluminium |

## Dimensions

| | | |
|---|---|---|
| Warning sphere diameter | (mm) | 600 |
| Warning sphere diameter | (inch) | 23.6 |

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications