PFISTERER

Warning Sphere
PA6, glass fiber reinforced, red / white

Features:

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.

Picture may vary.

Material:

- **Clamps:**
  Aluminium alloy with grooved channel
- **Hemisphere:**
  Coloured Polyamide 6 (PA6), glass fiber reinforced
- **Plates:**
  Stainless steel
- **Bolts:**
  Stainless steel
- **Safety plate:**
  Stainless steel

Technical Data

Article no.		180 542 484
Conductor diameter range	(mm)	50.9 - 52.2
Conductor diameter range	(inch)	2.00 - 2.06
Colour		red / white
Warning sphere material		Polyamide 6 (PA6), glass fiber reinforced
Clamp material		Aluminium

Dimensions

Warning sphere diameter	(mm)	600
Warning sphere diameter	(inch)	23.6

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications