

Warning Sphere

PA6, glass fiber reinforced, orange / white

Features:

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.



Material:

- **Clamps:**
Aluminium alloy with grooved channel
- **Hemisphere:**
Coloured Polyamide 6 (PA6), glass fiber reinforced
- **Plates:**
Stainless steel
- **Bolts:**
Stainless steel
- **Safety plate:**
Stainless steel

Picture may vary.

Technical Data

| | | |
|--------------------------|--------|---|
| Article no. | | 180 542 555 |
| Conductor diameter range | (mm) | 13.2 - 14.5 |
| Conductor diameter range | (inch) | 0.52 - 0.57 |
| Colour | | orange / white |
| Warning sphere material | | Polyamide 6 (PA6), glass fiber reinforced |
| Clamp material | | Aluminium |

Dimensions

| | | |
|-------------------------|--------|------|
| Warning sphere diameter | (mm) | 600 |
| Warning sphere diameter | (inch) | 23.6 |