PFISTERER

Warning Sphere Polyethylene, red

Features:

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.

Picture may vary.

Material:

- **Clamps:**
  Aluminium alloy with grooved channel
- **Hemisphere:**
  Coloured Polyethylene
- **Plates:**
  Stainless steel
- **Bolts:**
  Stainless steel
- **Safety plate:**
  Stainless steel

Technical Data

Article no.		180 544 274
Conductor diameter range	(mm)	37.9 - 39.2
Conductor diameter range	(inch)	1.49 - 1.54
Colour		red
Warning sphere material		Polyethylene
Clamp material		Aluminium

Dimensions

Warning sphere diameter	(mm)	600
Warning sphere diameter	(inch)	23.6

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications