© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Warning Sphere Polyethylene, white

Features:

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.



Material:

■ Clamps:

Aluminium alloy with grooved channel

Hemisphere:

Coloured Polyethylene

■ Plates:

Stainless steel

Bolts:

Stainless steel

Safety plate:

Stainless steel

Picture may vary.

Technical Data

| Article no. | | 180 544 350 |
|--------------------------|--------|--------------|
| Conductor diameter range | (mm) | 6.6 - 8.0 |
| Conductor diameter range | (inch) | 0.26 - 0.31 |
| Colour | | white |
| Warning sphere material | | Polyethylene |
| Clamp material | | Aluminium |

Dimensions

| Warning sphere diameter | (mm) | 600 |
|-------------------------|--------|------|
| Warning sphere diameter | (inch) | 23.6 |