

# Warning Sphere Polyethylene, red / white

**Features:**

- The warning sphere's colour is UV and Ozone resistant.
- The clamps feature a grooved channel, which makes slipping impossible.
- The warning sphere can be used for transmission and distribution lines of any voltage without any adjustment of the insulating distances.
- For aluminium based conductors and OPGW shield wires the warning sphere should be installed over armour rods.
- Drain holes prevent accumulation of rain inside the sphere.
- Nesting hemisphere design reduces transportation and storage costs.



*Picture may vary.*

**Material:**

- **Clamps:**  
Aluminium alloy with grooved channel
- **Hemisphere:**  
Coloured Polyethylene
- **Plates:**  
Stainless steel
- **Bolts:**  
Stainless steel
- **Safety plate:**  
Stainless steel

## Technical Data

|                                 |        |                    |
|---------------------------------|--------|--------------------|
| <b>Article no.</b>              |        | <b>180 544 450</b> |
| <b>Conductor diameter range</b> | (mm)   | 6.6 - 8.0          |
| <b>Conductor diameter range</b> | (inch) | 0.26 - 0.31        |
| <b>Colour</b>                   |        | red / white        |
| <b>Warning sphere material</b>  |        | Polyethylene       |
| <b>Clamp material</b>           |        | Aluminium          |

## Dimensions

|                                |        |      |
|--------------------------------|--------|------|
| <b>Warning sphere diameter</b> | (mm)   | 600  |
| <b>Warning sphere diameter</b> | (inch) | 23.6 |