

# Quad Spacer Damper

## Features

- maintains the design spacing between subconductors under normal service conditions
- controls the levels of aeolian vibration and subspan oscillation within the internationally accepted safety limits
- preserves mechanical elastic and damping properties over the entire service temperature range and for the expected lifetime of the line
- is maintenance-free for the whole lifetime of the line
- permits movement of the subconductors in any direction without damages of spacer components and subconductors strands
- maintains a suitable clamp grip and prevent clamp loosening by means of a safety plate and a belleville washer
- guarantees high corona extinction voltage due to proper clamp design and manufacturing
- withstand minimum short circuit current of 63 kA for 1 second



*Picture may vary.*

## Materials

- Body and clamps:  
high pressure die cast aluminium alloy
- Rubber elements:  
elastomer
- Bolts, nuts, plain washers:  
galvanized steel
- Belleville washers:  
mechanically galvanized steel
- Safety plates:  
stainless steel

## Clamp options

Component codes:

B Shear head caps

S Stainless steel bolts

BS Shear head caps and stainless steel bolts

## Orders with clamp options:

Orders for clamp options must be indicated with the component code of the desired clamp option at the end of the part number.

## Technical Data

Article no.	182 953 408	
Bundle Quantity	4	
Bundle Spacing	(mm)	400
Conductor diameter range	(mm)	25.5 - 26.8
Clamp type	Cantilever Clamp	