

# Link Box LB.W.X.7.1.S3.E0.060

PFISTERER's link boxes are key to reliable cross bonding and earthing concepts. The robust design withstands harsh operating conditions and contributes to high availability of plants. A wide product range and portfolio ensures maximum flexibility in planning of cable systems.



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>239 003 163</b>	
<b>Application</b>	<b>For wall type</b>	
<b>Material</b>	<b>Stainless Steel ANSI 304</b>	
<b>Link Box Type</b>	<b>Surge arrester</b>	
<b>Type of bonding lead</b>	<b>Single core cable</b>	
<b>Number of bonding cable entries</b>	<b>Three cables connected to the cable screen</b>	
<b>Number of earthing cable entries</b>	<b>Earth connected outside the box</b>	
<b>Rated voltage of surge arrester</b>	<b>U<sub>r</sub> (kV)</b>	<b>6</b>
<b>Number of phases</b>	<b>three-phase</b>	
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>)</b>	<b>70 - 150</b>
<b>Bonding cable conductor diameter</b>	<b>(mm)</b>	<b>9 - 14</b>
<b>Bonding cable overall diameter</b>	<b>(mm)</b>	<b>13 - 28</b>
<b>Protection Type</b>	<b>IP 66</b>	