

# Link Box LB.B.X.7.2.S3.E1.090

PFISTERER's link boxes are key to reliable cross bonding and earthing concepts. The robust design withstands harsh operating conditions and contributes to high availability of plants. A wide product range and portfolio ensures maximum flexibility in planning of cable systems.



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>239 003 184</b>	
<b>Application</b>	For underground type	
<b>Material</b>	Stainless Steel ANSI 304	
<b>Link Box Type</b>	Surge arrester	
<b>Type of bonding lead</b>	Coaxial cable	
<b>Number of bonding cable entries</b>	Three cables connected to the cable screen	
<b>Number of earthing cable entries</b>	One earth connected inside the box	
<b>Rated voltage of surge arrester</b>	U <sub>r</sub> (kV)	9
<b>Number of phases</b>	three-phase	
<b>Conductor cross section</b>	(mm <sup>2</sup> )	240 - 300
<b>Bonding cable conductor diameter</b>	(mm)	17 - 22
<b>Bonding cable overall diameter</b>	(mm)	42 - 50
<b>Earthing cable type</b>	Single core	
<b>Earthing cable diameter</b>	(mm)	14 - 25
<b>Earthing cable overall diameter</b>	(mm)	20 - 35
<b>Protection Type</b>	IP 68	