PFISTERER

# Link Box LB.B.X.3.2.S3.E1.050

PFISTERER's link boxes are key to reliable cross bonding and earthing concepts. The robust design withstands harsh operating conditions and contributes to high availability of plants. A wide product range and portfolio ensures maximum flexibility in planning of cable systems.

*Picture may vary.*

## Technical Data

| Article no. | | 239 003 233 |
|---|---|---|
| Application | | For underground type |
| Material | | Stainless Steel ANSI 304 |
| Link Box Type | | for cross bonding |
| Type of bonding lead | | Coaxial cable |
| Number of bonding cable entries | | Three cables connected to the cable screen |
| Number of earthing cable entries | | One earth connected inside the box |
| Rated voltage of surge arrester | $U_r$ (kV) | 5 |
| Conductor cross section | ($mm^2$) | 300 - 400 |
| Bonding cable conductor diameter | (mm) | 17 - 22 |
| Bonding cable overall diameter | (mm) | 49 -57 |
| Earthing cable type | | Single core |
| Earthing cable diameter | (mm) | 14 - 25 |
| Earthing cable overall diameter | (mm) | 27 - 45 |
| Protection Type | | IP 68 |

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications