PFISTERER

# Link Box LB.B.X.3.1.S6.E0.010

PFISTERER's link boxes are key to reliable cross bonding and earthing concepts. The robust design withstands harsh operating conditions and contributes to high availability of plants. A wide product range and portfolio ensures maximum flexibility in planning of cable systems.

*Picture may vary.*

## Technical Data

| Article no. | | 239 003 245 |
|---|---|---|
| Application | | For underground type |
| Material | | Stainless Steel ANSI 304 |
| Link Box Type | | for cross bonding |
| Type of bonding lead | | Single core cable |
| Number of bonding cable entries | | Six cables connected to the cable screen |
| Number of earthing cable entries | | Earth connected outside the box |
| Rated voltage of surge arrester | $U_r$ (kV) | 1 |
| Number of phases | | three-phase |
| Conductor cross section | ($mm^2$) | 95 - 240 |
| Bonding cable conductor diameter | (mm) | 12 - 17 |
| Bonding cable overall diameter | (mm) | 13 - 28 |
| Earthing cable type | | Single core |
| Earthing cable diameter | (mm) | 12 - 17 |
| Earthing cable overall diameter | (mm) | 13 - 28 |
| Protection Type | | IP 68 |

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications