

# Compression Die G06, DIN Hexagonal, Code Number 12, Al 16-25 mm<sup>2</sup> RM



Picture may vary.

## Technical Data

<b>Article no.</b>		<b>300 370 370</b>
Conductor cross sections Al non-rounded solid sector-shaped	(mm <sup>2</sup> )	-
Conductor cross sections Al rounded solid sector-shaped	(mm <sup>2</sup> )	35
Conductor cross sections Al full-tension	(mm <sup>2</sup> )	16 - 25
Code number		12
Compression width	(mm)	7
Standard		DIN 48083 T.4
AL-sleeve full tension ACSR	(mm <sup>2</sup> )	16/2,5 - 25/4
Conductor cross section, AL rounded solid sector-shaped, max.	(mm <sup>2</sup> )	35
Conductor cross section AL, non-tension stranded circular/stranded sector-shaped, max.	(mm <sup>2</sup> )	25
Conductor cross section AL, non-tension stranded circular/stranded sector-shaped, min.	(mm <sup>2</sup> )	16
Conductor cross section AL, full-tension, max.	(mm <sup>2</sup> )	25
Conductor cross section AL, full-tension, min.	(mm <sup>2</sup> )	16

## Dimensions

---

Width	(mm)	38
-------	------	----

---