PFISTERER

Compression Connector DIN 46267-2, Al 25 mm² RM/SM/RE

for non-tension connections.

For DIN 48201 compliant circular stranded aluminium conductors and circular stranded/sector-shaped stranded, circular solid and sector-shaped solid aluminium conductors in compliance with DIN VDE 0295.

Circular solid and sector-shaped solid aluminium conductors are to be compressed with mechanical crimping pliers only.

Sector-shaped conductors must be rounded with round-forming dies.
Al compression connectors are supplied prefilled with compression compound and packed in heat-sealed plastic bags.

Picture may vary.

Technical Data

Article no.		300 969 969
Type		non-tension Al
Conductor cross section Al solid circular	(mm²)	25
Conductor cross section Al stranded circular	(mm²)	25
Conductor cross section Al solid sector-shaped	(mm²)	35
Conductor cross section Al stranded sector-shaped	(mm²)	25
Diameter of conductor	Ø (mm)	5,6 - 6,6
Material		Al
Surface		uncoated
Code number		12
Number of compressions, mech. / hydr.		4-4/2-2
Oil stop		no

Dimensions

Dimension D	d (mm)	6,8
Dimension L	(mm)	70

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications