

# Compression Connector DIN 46267-2, Al 185 mm<sup>2</sup> RM/SM + 240 mm<sup>2</sup> SE

for non-tension connections.

For DIN 48201 compliant circular stranded aluminium conductors and circular stranded/sector-shaped stranded, circular solid and sector-shaped solid aluminium conductors in compliance with DIN VDE 0295.

Circular solid and sector-shaped solid aluminium conductors are to be compressed with mechanical crimping pliers only.

Sector-shaped conductors must be rounded with round-forming dies.  
Al compression connectors are supplied prefilled with compression compound and packed in heat-sealed plastic bags.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>300 976 976</b>	
<b>Type</b>	non-tension Al	
<b>Conductor cross section Al stranded circular</b>	(mm <sup>2</sup> )	185
<b>Conductor cross section Al solid sector-shaped</b>	(mm <sup>2</sup> )	240
<b>Conductor cross section Al stranded sector-shaped</b>	(mm <sup>2</sup> )	185
<b>Diameter of conductor</b>	Ø (mm)	15,5 - 18
<b>Material</b>	Al	
<b>Surface</b>	uncoated	
<b>Code number</b>	28	
<b>Number of compressions, mech. / hydr.</b>	6-6/3-3	
<b>Blind hole</b>	no	

## Dimensions

<b>Dimension D</b>	d (mm)	18,5
<b>Dimension L</b>	(mm)	125