

# Compression Connector DIN 48085, tension-proof, Al 35 mm<sup>2</sup>

For tension-proof connections in aluminium cables conforming to DIN 48201, Part 5.

**Material, surface:**

Al, bright

Dimensions in accordance with DIN 48085, Part 2.

Al pressure connectors are supplied filled with additive and sealed in film.



*Picture may vary.*

## Technical Data

|  |                              |
|--|------------------------------|
| <b>Article no.</b>   | <b>301 032 032</b>           |
| <b>Type</b>  | <b>tension-proof Al</b>      |
| <b>Conductor cross section</b>                                   | (mm <sup>2</sup> ) <b>35</b> |
| <b>Diameter of conductor</b>                                     | Ø (mm) <b>7,5</b>            |
| <b>Material</b>  | <b>Al</b>                    |
| <b>Surface</b>   | <b>uncoated</b>              |
| <b>Code number</b>   | <b>14</b>                    |
| <b>Number of compressions, mech. / hydr. narrow / hydr. wide</b> | <b>8-8 / - / -</b>           |
| <b>Blind hole</b>  | <b>no</b>                    |

## Dimensions

|                    |               |            |
|--------------------|---------------|------------|
| <b>Dimension D</b> | <b>d (mm)</b> | <b>8</b>   |
| <b>Dimension L</b> | <b>(mm)</b>   | <b>140</b> |