

# Cable Lug DIN 46235, 2xM12, 70 mm<sup>2</sup>, tin-plated

with 2 plate mounting holes for DIN 48201 compliant circular stranded copper cables.

**Material, Surface:**

Cu tinned



*Picture may vary.*

## Technical Data

|  |                    |                    |
|--|--------------------|--------------------|
| <b>Article no.</b>                           |                    | <b>304 756 756</b> |
| <b>Conductor cross section</b>               | (mm <sup>2</sup> ) | 70                 |
| <b>Diameter of terminal bolt</b>             | (mm)               | 12                 |
| <b>Diameter of conductor</b>                 | Ø (mm)             | 10,5               |
| <b>Surface</b>                               |                    | tin-plated         |
| <b>Code number</b>                           |                    | 16                 |
| <b>Number of compressions, mech. / hydr.</b> |                    | 3 / 1              |
| <b>Number of conductor</b>                   |                    | 1                  |
| <b>Material</b>                              |                    | Cu                 |

## Dimensions

|                     |                     |         |
|---------------------|---------------------|---------|
| <b>Hole spacing</b> | l <sub>2</sub> (mm) | 40 - 62 |
| <b>Dimension B</b>  | b (mm)              | 24      |
| <b>Diameter D1</b>  | Ø d1 (mm)           | 11,5    |
| <b>Diameter D2</b>  | Ø d2 (mm)           | 13      |
| <b>Dimension L1</b> | L <sub>1</sub> (mm) | 54      |