

# Cable Lug Sector Hole similar to DIN 46329, M12, 150 mm<sup>2</sup> SM + 185 mm<sup>2</sup> SE/RE, tin-plated

longitudinally sealed for sector-shaped stranded/sector-shaped solid aluminium conductors as well as circular solid aluminium conductors complying with DIN VDE 0295.

The sector-shaped conductors need not be round-formed.

**Material, surface:**

Al tinned

Al compression cable lugs are filled with compression compound and supplied in heat-sealed plastic bags. When fitting, in the case of bare Al compression cable lugs, clean the grooved bottom surface of the link with a wire brush before connecting.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>304 905 007</b>	
<b>Conductor cross section solid circular</b>	(mm <sup>2</sup> )	185
<b>Conductor cross section solid sector-shaped</b>	(mm <sup>2</sup> )	185
<b>Conductor cross section stranded sector-shaped</b>	(mm <sup>2</sup> )	150
<b>Diameter of terminal bolt</b>	(mm)	12
<b>Surface</b>	tin-plated	
<b>Code number</b>	27	
<b>Number of compressions, mech. / hydr.</b>	5 / 3	
<b>Material</b>	Al	

## Dimensions

<b>Diameter D1</b>	Ø d1 (mm)	13
<b>Diameter D2</b>	Ø d2 (mm)	30
<b>Dimension L</b>	(mm)	88