

# P3PS Panel Socket



Picture may vary.

## Technical Data

|   |  |
|---|--|
| <b>Article no.</b>                        | <b>305 007 308</b>                                       |
| <b>Size</b>                               | <b>P3</b>  |
| <b>Coding</b>                             | <b>AF08</b>  |
| <b>Connection type</b>                    | <b>Thread bolt M20 x 47</b>                              |
| <b>Thread bolt length</b>                 | <b>(mm) 47</b>   |
| <b>Material pressure nut</b>              | <b>Stainless steel (A2)</b>                              |
| <b>Safety washer</b>                      | <b>Yes</b>   |
| <b>Rated voltage AC - effective value</b> | <b>(kV) 4.4</b>  |
| <b>Test impulse voltage AC</b>            | <b>(kV) 15 (EN 50124-1, Tab. A2)</b>                     |
| <b>Rated current</b>                      | <b>(A) 1250 (DIN EN 60512-5-2, 20 Celsius degree)</b>    |
| <b>High short circuit strength</b>        | <b>(kA / 2 sec) 16,7</b>                                 |
| <b>Protection Type</b>                    | <b>IP 67 (DIN EN 60529)</b>                              |
| <b>Operating temperature</b>              | <b>(°C) -40 ... +125</b>                                 |
| <b>Weight</b>                             | <b>(g) 920</b>   |
| <b>Flame-resistant</b>                    | <b>UNI CEI 11170-3<br/>NF F16-101<br/>CEN/TS 45545-2</b> |