

# Compression Connectors High Voltage similar to DIN 46267-1, 120 mm<sup>2</sup> RM/SM

with through hole for non-tension connections of medium-voltage cables.

The compression joints are suitable for paper and plastic-insulated cables. They have double markings and can be either round compressed or hexagonally compressed, depending on the cable type and voltage level.



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>305 306 001</b>
<b>Type</b>	<b>non-tension Cu</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 120</b>
<b>Diameter of conductor</b>	<b>Ø (mm) 14</b>
<b>Material</b>	<b>Cu</b>
<b>Surface</b>	<b>uncoated</b>
<b>Number of compressions, hexagonal hydraulic</b>	<b>2-2</b>
<b>Number of compressions, hexagonal mech.</b>	<b>4-4</b>
<b>Code number round</b>	<b>18 HR</b>
<b>Code number hexagonal</b>	<b>20</b>
<b>Blind hole</b>	<b>no</b>

## Dimensions

<b>Dimension D</b>	<b>d (mm)</b>	<b>15,5</b>
<b>Dimension L</b>	<b>(mm)</b>	<b>90</b>