

# Compression Connector High Voltage similar to DIN 46267-2, 150 mm<sup>2</sup> RM/SM

with through-hole for non-tension connections of medium-voltage cables.  
The compression joints are suitable for paper- and plastic-insulated cables. They bear double markings and can be either round compressed or hexagonally compressed, depending on cable type and voltage level.



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>305 337 001</b>
<b>Type</b>	<b>non-tension Al</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 150</b>
<b>Diameter of conductor</b>	<b>Ø (mm) 15,7</b>
<b>Material</b>	<b>Al</b>
<b>Surface</b>	<b>uncoated</b>
<b>Number of compressions, hexagonal hydraulic</b>	<b>2-2</b>
<b>Number of compressions, hexagonal mech.</b>	<b>4-4</b>
<b>Code number round</b>	<b>22 HR</b>
<b>Code number hexagonal</b>	<b>25</b>
<b>Blind hole</b>	<b>no</b>

## Dimensions

<b>Dimension D1</b>	<b>d<sub>1</sub> (mm)</b>	<b>105</b>
<b>Dimension D</b>	<b>d (mm)</b>	<b>16,5</b>
<b>Dimension L</b>	<b>(mm)</b>	<b>105</b>