

Cable Lug Al/Cu, similar to DIN 46329, M12, 300 mm² RM/SM

For DIN 48201 compliant stranded circular aluminium cables and stranded circular/stranded sector-shaped, solid circular in compliance with DIN VDE 0295 solid sector-shaped conductors. DIN 46329 compliant aluminium compression sleeve.

Material, Surface:

Al and Cu uncoated

Advantages

- age-resistant current passage from the aluminium shaft to the solid copper terminal plate
- the mounting hole can be adjusted to different bolt diameters
- specially designed to minimise corrosion due to electrolytic action on the Al and Cu
- specially designed to provide longitudinal sealing of the compression cable lugs.



Picture may vary.

Sector-shaped conductors SM/SE have to be round-pressed by using round-compressing inserts. Solid Al conductors RE/SE should only be compressed with mechanical hand crimping pliers. Al compression cable lugs are filled with compression additive and are supplied shrink-wrapped.

Technical Data

Article no.		305 668 028
Conductor cross section stranded circular	(mm ²)	300
Conductor cross section stranded sector-shaped	(mm ²)	300
Diameter of terminal bolt	(mm)	12
Surface		uncoated
Code number		34
Number of compressions, mech. / hydr.		8 / 3
Material		Al/Cu