

Compression Connector Al/Cu, Al 95 mm² RM/ SM + 120 mm² SE / Cu 70 mm² RM/SM

with blind hole for non-tension connections of low and high voltage cables with plastic and paper insulation.

The Al/Cu compression joints are compressed hexagonally. The blind hole prevents any oil escaping from where the plastic insulated cables meet paper insulated cables.

Material, Surface:

Al/Cu uncoated



Picture may vary.

Technical Data

Article no.	305 835 002
Type	non-tension Al/Cu
Conductor cross section Al stranded circular	(mm ²) 95
Conductor cross section Al solid sector-shaped	(mm ²) 120
Conductor cross section Al stranded sector-shaped	(mm ²) 95
Conductor cross section Cu	(mm ²) 70
Conductor diameter Al d1	Ø (mm) 12,5
Conductor diameter Cu d2	Ø (mm) 10,5
Material	Al/Cu
Surface	uncoated
Number of compressions Al mech./hydr., Cu mech./hydr.	6/3, 3/1
Code number Al / Cu	22 / 16
Code number Al	22
Tool code number Cu	16
Oil stop	yes

Dimensions

Diameter D1	Ø d1 (mm)	13,2
Diameter D2	Ø d2 (mm)	11,5
Dimension L	(mm)	101