

# Cable Lug Al/Cu, similar to DIN 46329, Sector Hole, M10, 50 mm<sup>2</sup> SM + 70 mm<sup>2</sup> SE/RE

longitudinally sealed for sector-shaped stranded/sector-shaped solid aluminium conductors as well as circular solid aluminium conductors complying with DIN VDE 0295.

The sector-shaped conductors need not be round-formed.

**Material, surface:**

Al, Cu bare

Al compression cable lugs are filled with compression compound and supplied in heat-sealed plastic bags.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>305 865 003</b>	
<b>Conductor cross section solid circular</b>	(mm <sup>2</sup> )	70
<b>Conductor cross section solid sector-shaped</b>	(mm <sup>2</sup> )	70
<b>Conductor cross section stranded sector-shaped</b>	(mm <sup>2</sup> )	50
<b>Diameter of terminal bolt</b>	(mm)	10
<b>Surface</b>	uncoated	
<b>Code number</b>	18	
<b>Number of compressions, mech. / hydr.</b>	4 / 2	
<b>Material</b>	Al/Cu	

## Dimensions

<b>Diameter D2</b>	Ø d2 (mm)	13
<b>Diameter D3</b>	Ø d3 (mm)	25
<b>Dimension L</b>	(mm)	85