PFISTERER

Compression Connector Al/Cu, Al 150 mm² RM/SM + 185 mm² SE / Cu 120 mm² RM/SM

with blind hole for non-tension connections of low and high voltage cables with plastic and paper insulation.

The Al/Cu compression joints are compressed hexagonally. The blind hole prevents any oil escaping from where the plastic insulated cables meet paper insulated cables.

Material, Surface:
Al/Cu uncoated

Picture may vary.

Technical Data

Article no.		305 881 002
Type		non-tension Al/Cu
Conductor cross section Al stranded circular	(mm²)	150
Conductor cross section Al solid sector-shaped	(mm²)	185
Conductor cross section Al stranded sector-shaped	(mm²)	150
Conductor cross section Cu	(mm²)	120
Conductor diameter Al d1	Ø (mm)	15,8
Conductor diameter Cu d2	Ø (mm)	14
Material		Al/Cu
Surface		uncoated
Number of compressions Al mech./hydr., Cu mech./hydr.		6/3, 4/2
Code number Al / Cu		25 / 20
Code number Al		25
Tool code number Cu		20
Oil stop		yes

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Diameter D1	**Ø d1 (mm)**	**16,3**
Diameter D2	**Ø d2 (mm)**	**15,5**
Dimension L	**(mm)**	**120**

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications