

Connecta II Four Core Connection Clamp 4 x 25 - 150 mm²

Properties:

- Multiple range use (SM, SE, RM and RE conductors)
- Applicable on Al and Cu conductors
- Compact, space-saving design, developed for all common resin based plastic and cast iron sleeves
- Simple, time-saving assembly without special tools
- No round pressing of sector conductors
- Contacting using SICON NG shear bolts
- Tested according to IEC 61238-1

Material:

Connector body: Al-Alloy (AlMgSi), tin-plated
Screws: brass (CuZn)



Picture may vary.

Technical Data

Article no.		332 149 001
Conductor cross section Al RE	(mm ²)	25 - 150
Conductor cross section Al RM	(mm ²)	25 - 150
Conductor cross section Al SE	(mm ²)	25 - 150
Conductor cross section Al SM	(mm ²)	25 - 150
Conductor cross section Cu RE	(mm ²)	25 - 150
Conductor cross section Cu RM	(mm ²)	25 - 150
Conductor cross section Cu SM	(mm ²)	25 - 150
Shear-off torque	(Nm)	35 +/- 4
Width across flats		SW6
Screw Type		shear bolt

Dimensions

Circumscribed circle diameter	(mm)	74
Core diameter	Ø (mm)	19,3
Dimension L	(mm)	85