PFISTERER

Connection clamp Al with blind hole

for copper and aluminium conductors.
Specially-developed for creating connections for heat shrinking processes.

Material:
Aluminium alloy (AlMgSi), uncoated
Brass bolts (CuZn), tin-plated

Picture may vary.

Technical Data

Article no.		332 312 004
Conductor cross section Al RE	(mm^2)	35 - 150
Conductor cross section Al RM	(mm^2)	35 - 150
Conductor cross section Al SE	(mm^2)	35 - 150
Conductor cross section Al SM	(mm^2)	35 - 120
Conductor cross section Cu RE	(mm^2)	35 - 150
Conductor cross section Cu RM	(mm^2)	35 - 150
Conductor cross section Cu SM	(mm^2)	35 - 120
Inspection hole		no
Oil stop		yes
Shear head		yes
Number of screws		2
Width across flats		SW 6
Screw Type		shear bolt
Torque	(Nm)	25
Surface		uncoated
Packing unit		pcs

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Diameter D1	**Ø d1 (mm)**	**28**
Diameter D2	**Ø d2 (mm)**	**18,5**
Dimension L	**(mm)**	**70**

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications