

# ABC Tap Connectors

Plastic connector of plastic with inserted contact plates, suitable for installation on live lines. When tightening the screws, the teeth on the contact plates penetrate the insulation and establish a contact that is resistant to constant current. The conductors do not need to be stripped. Clamp channel covers cover the conductor ends to the outer edges of the clamp. If covers are not needed, they can easily be broken off cleanly.

Suitable for aluminium and copper main and tap-off conductors.

## Material:

Contact plates: copper alloy

Body: fibre glass reinforced plastic material

Pressure plates and screws: steel, hot- galvanized



*Picture may vary.*

## Technical Data

Article no.		332 350 002
Cross section of main conductor	(mm <sup>2</sup> )	16 - 95
Conductor cross section Al stranded circular	(mm <sup>2</sup> )	16 - 95
Conductor cross section Cu stranded circular	(mm <sup>2</sup> )	16 - 95
Cross section of tap conductor	(mm <sup>2</sup> )	6 - 35
Screw		M8
Tap covers		2
Main conductor/ tap covers		2 / 2
Main conductor covers		2
Number of screws		1
Number of bolts		1 x M8
Torque	(Nm)	15

## Dimensions

Dimension B	b (mm)	43
Dimension L1	L <sub>1</sub> (mm)	32