PFISTERER

1 kV cast resin joint set 130/300 for 4 wire cable including ISICOMPACT tap connector 331 896 003

*At 150 mm^2 round stranded main cables only 6 - 25 mm^2 solid sector-shaped / stranded sector-shaped, 6 - 35 mm^2 round stranded and 6 - 50 mm^2 round solid tap cables are possible.

Picture may vary.

Technical Data

Article no.		332 407 114
Main cable diameter max.	(mm)	50
Number of wires main cable		4
Conductor cross section Al solid circular	(mm^2)	70 - 150
Conductor cross section Cu solid circular	(mm^2)	70 - 150
Conductor cross section Al stranded circular	(mm^2)	70 - 150*
Conductor cross section Cu stranded circular	(mm^2)	70 - 150*
Conductor cross section Al solid sector-shaped	(mm^2)	70 - 185
Conductor cross section Al stranded sector-shaped	(mm^2)	70 - 150
Conductor cross section Cu stranded sector-shaped	(mm^2)	50 - 150
Branch cable diameter	(mm)	32
Cross section of tap conductor	(mm^2)	6 - 50 + 70SE*
Suitable for cable types		N(A)2XY, N(A)2X2Y, N(A)YY, N(A)Y2Y
Compact tap connector		331896003
Joint model		130/300
Shell material		Polycarbonate
Cast resin type		KP-PUR 2000

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Article no.		**332 407 114**
Cast resin container		**Tins**
Cast resin volume	**(l)**	**2,1**

Dimensions

Joint body diameter	**(mm)**	**130**
External length	**(mm)**	**300**
Internal length	**(mm)**	**235**

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications