

1 kV cast resin joint set 165/450 for 4 wire cable including ISICOMPACT tap connector 331 897 001 00006



Picture may vary.

Technical Data

Article no.		332 407 142
Main cable diameter max.	(mm)	65
Number of wires main cable		4
Conductor cross section Al solid sector-shaped	(mm ²)	95 - 240
Conductor cross section Al stranded sector-shaped	(mm ²)	95 - 240
Conductor cross section Cu stranded sector-shaped	(mm ²)	95 - 240
Branch cable diameter	(mm)	55
Cross section of tap conductor with Al solid sector-shaped main conductor	(mm ²)	35 - 185 mm ² Al SE, 35 - 95 mm ² Al SM/RM, 25 - 150 mm ² Al RE / Cu
Cross section of tap conductor with stranded sector-shaped main conductor	(mm ²)	35 - 150 mm ² Al SE, 25 - 150 mm ² Al RE, 25 - 95 mm ² RM/SM / Cu RE
Suitable for cable types		N(A)YY
Compact tap connector		33189700100006
Joint model		165/450
Shell material		Polycarbonate
Cast resin type		KP-PUR 2000
Cast resin container		Tins
Cast resin volume	(l)	5,7

Dimensions

Joint body diameter	(mm)	165
External length	(mm)	450
Internal length	(mm)	390