

1 kV cast resin joint set 130/300 for 4 and 3½ wire cable including ISICOMPACT tap connector 331 896 031

*At 150 mm² round stranded main cables only 6 - 25 mm² solid sector-shaped / stranded sector-shaped, 6 - 35 mm² round stranded and 6 - 50 mm² round solid tap cables are possible.



Picture may vary.

Technical Data

Article no.		332 407 152
Main cable diameter max.	(mm)	50
Number of wires main cable		4, 3 1/2
Conductor cross section Al solid circular	(mm ²)	4 x 35 - 150
Conductor cross section Cu solid circular	(mm ²)	4 x 35 - 150
Conductor cross section Al stranded circular	(mm ²)	4 x 25 - 150, 3 x 70/35 - 150/70 (95)*
Conductor cross section Cu stranded circular	(mm ²)	4 x 25 - 150, 3 x 70/35 - 150/70 (95)*
Conductor cross section Al solid sector-shaped	(mm ²)	4 x 50 - 185
Conductor cross section Al stranded sector-shaped	(mm ²)	4 x 35 - 150, 3 x 70/35 - 150/70 (95)
Conductor cross section Cu stranded sector-shaped	(mm ²)	4 x 35 - 150, 3 x 70/35 - 150/70 (95)
Branch cable diameter	(mm)	32
Cross section of tap conductor	(mm ²)	6 - 50 + 70SE*
Suitable for cable types		N(A)2XY, N(A)2X2Y, N(A)YY, N(A)Y2Y
Compact tap connector		331896031
Joint model		130/300
Shell material		Polycarbonate
Cast resin type		KP-PUR 2000

Article no.	332 407 152
Cast resin container	Tins
Cast resin volume	(l) 2,1

Dimensions

Joint body diameter	(mm) 130
External length	(mm) 300
Internal length	(mm) 235