

1 kV cast resin joint set 130/300 for 4 wire cable including ISICOMPACT tap connector 331 896 003

according to E.ON specification.



Picture may vary.

Technical Data

Article no.		332 408 311
Main cable diameter max.	(mm)	50
Number of wires main cable		4
Conductor cross section Al solid circular	(mm ²)	70 - 150
Conductor cross section Cu solid circular	(mm ²)	70 - 150
Conductor cross section Al stranded circular	(mm ²)	70 - 150
Conductor cross section Cu stranded circular	(mm ²)	70 - 150
Conductor cross section Al solid sector-shaped	(mm ²)	70 - 185
Conductor cross section Al stranded sector-shaped	(mm ²)	70 - 150
Conductor cross section Cu stranded sector-shaped	(mm ²)	50 - 150
Branch cable diameter	(mm)	32
Cross section of tap conductor	(mm ²)	6 - 50 + 70SE
Suitable for cable types		N(A)2XY, N(A)2X2Y, N(A)YY, N(A)Y2Y
Compact tap connector		331896003
Joint model		130/300
Shell material		Polycarbonate
Cast resin type		KP-PUR 762

Article no.	332 408 311	
Cast resin container	Tins	
Cast resin volume	(l)	2,1

Dimensions

Joint body diameter	(mm)	130
External length	(mm)	300
Internal length	(mm)	235