PFISTERER

Connection clamp Al with blind hole

for copper and aluminium conductors.
Specially-developed for creating connections for heat shrinking processes.

Material:
Aluminium alloy (AlMgSi), uncoated
Brass bolts (CuZn), tin-plated

Picture may vary.

Technical Data

Article no.		332 409 001
Conductor cross section Al RE	(mm^2)	120 - 240
Conductor cross section Al RM	(mm^2)	120 - 240
Conductor cross section Al SE	(mm^2)	120 - 240
Conductor cross section Al SM	(mm^2)	120 - 240
Conductor cross section Cu RE	(mm^2)	120 - 240
Conductor cross section Cu RM	(mm^2)	120 - 240
Conductor cross section Cu SM	(mm^2)	120 - 240
Inspection hole		no
Oil stop		yes
Shear head		no
Number of screws		4
Width across flats		SW 6
Screw Type		grub screw
Torque	(Nm)	25
Surface		uncoated
Packing unit		pcs

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Diameter D1	**Ø d1 (mm)**	**38**
Diameter D2	**Ø d2 (mm)**	**22,5**
Dimension L	**(mm)**	**128**

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications