

# Connection clamp Al with blind hole

for copper and aluminium conductors.  
Specially-developed for creating connections for heat shrinking processes.

**Material:**

Aluminium alloy (AlMgSi), uncoated  
Brass bolts (CuZn), tin-plated



*Picture may vary.*

## Technical Data

<b>Article no.</b>		<b>332 409 001</b>
Conductor cross section Al RE	(mm <sup>2</sup> )	120 - 240
Conductor cross section Al RM	(mm <sup>2</sup> )	120 - 240
Conductor cross section Al SE	(mm <sup>2</sup> )	120 - 240
Conductor cross section Al SM	(mm <sup>2</sup> )	120 - 240
Conductor cross section Cu RE	(mm <sup>2</sup> )	120 - 240
Conductor cross section Cu RM	(mm <sup>2</sup> )	120 - 240
Conductor cross section Cu SM	(mm <sup>2</sup> )	120 - 240
Shear head		no
Number of screws		4
Torque	(Nm)	25
Surface		uncoated
Width across flats		SW 6
Screw Type		stud screw
Inspection hole		no
Blind hole		yes
Packing unit		pcs

## Dimensions

Diameter D1	Ø d1 (mm)	38
Diameter D2	Ø d2 (mm)	22,5
Dimension L	(mm)	128