

# 1 kV cast resin joint set 130/300 for 4 wire cable including ISICOMPACT tap connector 331 896 011

according to E.ON specification.



Picture may vary.

## Technical Data

<b>Article no.</b>		<b>332 409 302</b>
<b>Main cable diameter max.</b>	(mm)	50
<b>Number of wires main cable</b>		4
<b>Conductor cross section Al solid circular</b>	(mm <sup>2</sup> )	35 - 95
<b>Conductor cross section Cu solid circular</b>	(mm <sup>2</sup> )	35 - 95
<b>Conductor cross section Al stranded circular</b>	(mm <sup>2</sup> )	25 - 95
<b>Conductor cross section Cu stranded circular</b>	(mm <sup>2</sup> )	25 - 95
<b>Conductor cross section Al solid sector-shaped</b>	(mm <sup>2</sup> )	35 - 95
<b>Conductor cross section Al stranded sector-shaped</b>	(mm <sup>2</sup> )	35 - 95
<b>Conductor cross section Cu stranded sector-shaped</b>	(mm <sup>2</sup> )	35 - 95
<b>Branch cable diameter</b>	(mm)	32
<b>Cross section of tap conductor</b>	(mm <sup>2</sup> )	6 - 50 + 70SE
<b>Suitable for cable types</b>		N(A)2XY, N(A)2X2Y, N(A)YY, N(A)Y2Y
<b>Compact tap connector</b>		331896011
<b>Joint model</b>		130/300
<b>Shell material</b>		Polycarbonate
<b>Cast resin type</b>		KP-FILL BRH

<b>Article no.</b>		<b>332 409 302</b>
<b>Cast resin container</b>		<b>Tins</b>
<b>Cast resin volume</b>	<b>(l)</b>	<b>2,1</b>

## Dimensions

<b>Joint body diameter</b>	<b>(mm)</b>	<b>130</b>
<b>External length</b>	<b>(mm)</b>	<b>300</b>
<b>Internal length</b>	<b>(mm)</b>	<b>235</b>