

1 kV cast resin joint set 130/300 for 4 wire cable including ISICOMPACT tap connector 331 896 011

according to E.ON CZ specification.



Picture may vary.

Technical Data

| | | |
|--|--------------------|---|
| Article no. | | 332 409 402 |
| Main cable diameter max. | (mm) | 50 |
| Number of wires main cable | | 4 |
| Conductor cross section Al solid circular | (mm ²) | 35 - 95 |
| Conductor cross section Cu solid circular | (mm ²) | 35 - 95 |
| Conductor cross section Al stranded circular | (mm ²) | 25 - 95 |
| Conductor cross section Cu stranded circular | (mm ²) | 25 - 95 |
| Conductor cross section Al solid sector-shaped | (mm ²) | 35 - 95 |
| Conductor cross section Al stranded sector-shaped | (mm ²) | 35 - 95 |
| Conductor cross section Cu stranded sector-shaped | (mm ²) | 35 - 95 |
| Branch cable diameter | (mm) | 32 |
| Cross section of tap conductor | (mm ²) | 6 - 50 + 70 SE |
| Suitable for cable types | | N(A)2XY, N(A)2X2Y, N(A)YY, N(A)Y2Y |
| Compact tap connector | | 331896011 |
| Joint model | | 130/300 |
| Shell material | | Polycarbonate |
| Cast resin type | | KP-FILL BRH |

| | | |
|----------------------|-------------|-----|
| Article no. | 332 409 402 | |
| Cast resin container | Mixing bags | |
| Cast resin volume | (l) | 2,1 |

Dimensions

| | | |
|---------------------|------|-----|
| Joint body diameter | (mm) | 130 |
| External length | (mm) | 300 |
| Internal length | (mm) | 235 |