

## One-Core Cold-Shrink Hybrid Joint, 12/24 kV, 800-1000 mm<sup>2</sup>, without Bolted Connector

for XLPE cable with copper wire screen.

### Material:

- durable silicone rubber

### Advantages:

- Reliable contacting of all conductors
- Optimum contact force for all conductors
- No damage to individual conductors
- Mounting with standard tools
- Excellent insulation
- Wide range of application
- Tested according to HD 629

### Scope of delivery:

- Cold shrink body with integrated electrodes for field control
- Screen connection components
- Heat shrink outer tubes
- Cleaning wipes, sanding paper, grease, etc.

### Attention:

The bolted connector is **not** included in the scope of delivery and has to be ordered separately.



*Picture may vary.*

## Technical Data

|                                     |                                    |
|-------------------------------------|------------------------------------|
| <b>Article no.</b>                  | <b>332 730 106</b>                 |
| <b>Designation</b>                  | <b>PCHJ 12-24/800-1000-1</b>       |
| <b>Cable cross section at 12 kV</b> | <b>(mm<sup>2</sup>) 800 - 1000</b> |
| <b>Cable cross section at 24 kV</b> | <b>(mm<sup>2</sup>) 800 - 1000</b> |
| <b>Insulation diameter min.</b>     | <b>(mm) 36.8</b>                   |
| <b>Insulation diameter max.</b>     | <b>(mm) 58.0</b>                   |
| <b>Recommended bolted connector</b> | <b>332 590 074</b>                 |
| <b>Bolted connector included</b>    | <b>no</b>                          |