

## One-Core Cold-Shrink Hybrid Joint, 12/24 kV, 50-240 mm<sup>2</sup>, with SICON Bolted Connector (332 592 012)

for XLPE cable with copper wire screen.

### Material:

- durable silicone rubber

### Advantages:

- Reliable contacting of all conductors
- Optimum contact force for all conductors
- No damage to individual conductors
- Mounting with standard tools
- Excellent insulation
- Wide range of application
- Tested according to HD 629

### Scope of delivery:

- SICON bolted connector
- Cold shrink body with integrated electrodes for fieldcontrol
- Screen connection components
- Heat shrink outer tubes
- Cleaning wipes, sanding paper, grease, etc.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>332 730 201</b>
<b>Designation</b>	<b>PCHJ-C 12-24/50-240-1</b>
<b>Cable cross section at 12 kV</b>	(mm <sup>2</sup> ) 95 - 240
<b>Cable cross section at 24 kV</b>	(mm <sup>2</sup> ) 50 - 240
<b>Insulation diameter min.</b>	(mm) 18.4
<b>Insulation diameter max.</b>	(mm) 36.0
<b>Recommended bolted connector</b>	332 592 012
<b>Bolted connector included</b>	yes