

## One-Core Cold-Shrink Hybrid Joint, 36/42 kV, 25-95 mm<sup>2</sup>, without Bolted Connector

for XLPE cable with copper wire screen.

### Material:

- durable silicone rubber

### Advantages:

- Reliable contacting of all conductors
- Optimum contact force for all conductors
- No damage to individual conductors
- Mounting with standard tools
- Excellent insulation
- Wide range of application
- Tested according to HD 629

### Scope of delivery:

- Cold shrink body with integrated electrodes for field control
- Screen connection components
- Heat shrink outer tubes
- Cleaning wipes, sanding paper, grease, etc.

### Attention:

The bolted connector is **not** included in the scope of delivery and has to be ordered separately.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>332 730 300</b>
<b>Designation</b>	<b>PCHJ 36-42/25-95-1</b>
<b>Cable cross section at 36 kV</b>	(mm <sup>2</sup> ) 25 - 95
<b>Cable cross section at 42 kV</b>	(mm <sup>2</sup> ) 25 - 95
<b>Insulation diameter min.</b>	(mm) 20.8
<b>Insulation diameter max.</b>	(mm) 36.0
<b>Recommended bolted connector</b>	332 601 122
<b>Bolted connector included</b>	no