

One-Core Indoor Cold-Shrink Termination, 36/42 kV, 240-400 mm², without Bolted Cable Lug

for XLPE cable with copper wire screen.

Material:


- Silicone

Benefits:

- Reliable contact of all conductors
- Optimum contact force for all conductors
- No damage to individual conductors
- Excellent insulation
- Self-cleaning and maintenance-free
- Wide range of application
- Tested according to HD 629.1 S2

Attention:

The cable lug is **not** included in the scope of delivery and has to be ordered separately.



Picture may vary.

Technical Data

Article no.	332 731 304
Designation	PCIT 36-42/240-400-1
Working place	indoor
Cable cross section at 36 kV	(mm ²) 240 - 400
Cable cross section at 42 kV	(mm ²) 240 - 400
Recommended cable lug	332 625 012
Cable lug included	no
Coldshrink body type	CTSB
Min. diameter insulation / cable lug	(mm) 35.1
Max. diameter insulation / cable lug	(mm) 61
Max. width lug blade	(mm) 60
Number of sheds	3

Dimensions

Creepage length C, +/- 20 mm	(mm)	640
Termination length L, +/- 10 mm	(mm)	450
Body inner diameter D1, +/- 1 mm	(mm)	27
Spiral inner diameter D2, +/- 2 mm	(mm)	70
Shed diameter D3, +/- 5 mm	(mm)	100