

One-Core Outdoor Cold-Shrink Termination, 36/42 kV, 70-240 mm², with SICON Bolted Cable Lug (332 595 012)

for XLPE cable with copper wire screen.

Material:

- Silicone

Benefits:

- Reliable contact of all conductors
- Optimum contact force for all conductors
- No damage to individual conductors
- Excellent insulation
- Self-cleaning and maintenance-free
- Wide range of application
- Tested according to HD 629.1 S2



Picture may vary.

Technical Data

Article no.	332 732 402
Designation	PC0T-C 36-42/70-240-1
Working place	outdoor
Cable cross section at 36 kV	(mm²) 120 - 240
Cable cross section at 42 kV	(mm²) 70 - 240
Recommended cable lug	332 595 012
Cable lug included	yes
Coldshrink body type	CTSB + CTSC
Min. diameter insulation / cable lug	(mm) 28.6
Max. diameter insulation / cable lug	(mm) 50
Max. width lug blade	(mm) 55
Number of sheds	6

Dimensions

Creepage length C, +/- 20 mm	(mm)	1060
Termination length L, +/- 10 mm	(mm)	680
Body inner diameter D1, +/- 1 mm	(mm)	22
Spiral inner diameter D2, +/- 2 mm	(mm)	65
Shed diameter D3, +/- 5 mm	(mm)	100