PFISTERER

Low Voltage Screw Connector, tin-plated, without blind hole

These screw connectors meet the requirements under DIN 47640 for heat-shrinkable technology. However they can be used for all other forms of joint.

Picture may vary.

Technical Data

Article no.		332 802 002
Conductor cross section Al RE	(mm^2)	25 - 150
Conductor cross section Al RM	(mm^2)	25 - 150
Conductor cross section Al RMv	(mm^2)	25 - 150
Conductor cross section Al SE	(mm^2)	25 - 185
Conductor cross section Al SM	(mm^2)	25 - 150
Conductor cross section Cu RE	(mm^2)	25 - 150
Conductor cross section Cu RM	(mm^2)	25 - 150
Conductor cross section RMv	(mm^2)	25 - 150
Conductor cross section Cu SM	(mm^2)	25 - 150
Number of screws		2
Surface		tin-plated
Width across flats		8
Screw		M18 x 1
Screw Type		shear bolt
Inspection hole		yes
Blind hole		no

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Outer diameter	**Ø (mm)**	**28**
Core diameter	**Ø (mm)**	**16,3**
Body Length	**(mm)**	**60**

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications