

# Low Voltage Screw Connector, tin-plated, without blind hole

These screw connectors meet the requirements under DIN 47640 for heat-shrinkable technology. However they can be used for all other forms of joint.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>332 804 002</b>	
<b>Conductor cross section Al RE</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Al RM</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Al RMv</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Al SE</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Al SM</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Cu RE</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Cu RM</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section RMv</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Conductor cross section Cu SM</b>	(mm) <sup>2</sup>	<b>25 - 95</b>
<b>Inspection hole</b>	<b>yes</b>	
<b>Oil stop</b>	<b>no</b>	
<b>Number of screws</b>	<b>2</b>	
<b>Width across flats</b>	<b>8</b>	
<b>Screw</b>	<b>M14 x 1</b>	
<b>Screw Type</b>	<b>shear bolt</b>	
<b>Surface</b>	<b>tin-plated</b>	

## Dimensions

<b>Outer diameter</b>	<b>Ø (mm)</b>	<b>25</b>
<b>Core diameter</b>	<b>Ø (mm)</b>	<b>13</b>
<b>Body Length</b>	<b>(mm)</b>	<b>50</b>