

# Low Voltage Screw Connector, tin-plated, with blind hole

These screw connectors meet the requirements under DIN 47640 for heat-shrinkable technology. However they can be used for all other forms of joint.



*Picture may vary.*

## Technical Data

<b>Article no.</b>		<b>332 805 802</b>
<b>Conductor cross section Al RE</b>	(mm <sup>2</sup> )	25 - 185
<b>Conductor cross section Al RM</b>	(mm <sup>2</sup> )	25 - 185
<b>Conductor cross section Al SE</b>	(mm <sup>2</sup> )	25 - 150, 185 (90°)
<b>Conductor cross section Al SM</b>	(mm <sup>2</sup> )	25 - 120, 150 (90°)
<b>Conductor cross section Cu RE</b>	(mm <sup>2</sup> )	25 - 185
<b>Conductor cross section Cu RM</b>	(mm <sup>2</sup> )	25 - 185
<b>Conductor cross section Cu SM</b>	(mm <sup>2</sup> )	25 - 120, 150 (90°)
<b>Number of screws</b>		2
<b>Surface</b>		tin-plated
<b>Width across flats</b>		8
<b>Screw</b>		M18
<b>Screw Type</b>		stud screw
<b>Inspection hole</b>		no
<b>Blind hole</b>		yes

## Dimensions

<b>Outer diameter</b>	<b>Ø (mm)</b>	<b>32</b>
<b>Body Length</b>	<b>(mm)</b>	<b>80</b>