

Low Voltage Screw Connectors, tin-plated, without blind hole

These screw connectors meet the requirements under DIN 47640 for heat-shrinkable technology. However they can be used for all other forms of joint.



Picture may vary.

Technical Data

Article no.		332 806 002
Conductor cross section Al solid circular	(mm ²)	95 - 240
Conductor cross section Al stranded circular	(mm ²)	95 - 240
Conductor cross section Al stranded circular compressed	(mm ²)	95 - 240
Conductor cross section Al solid sector-shaped	(mm ²)	95 - 240
Conductor cross section Al stranded sector-shaped	(mm ²)	95 - 240
Conductor cross section Cu solid circular	(mm ²)	95 - 240
Conductor cross section Cu stranded circular	(mm ²)	95 - 240
Conductor cross section Cu stranded circular compressed	(mm ²)	150 - 240
Conductor cross section Cu stranded sector-shaped	(mm ²)	150 - 240
Outer diameter	Ø (mm)	37
Shear bolts		yes
Number of screws		4
Core diameter	Ø (mm)	22
Body Length	(mm)	126
Surface		tinned
Width across flats		8
Screw		M18 x 1
Screw Type		shear bolt

Article no.	332 806 002
Inspection hole	yes
Blind hole	no